

Honeywell

Material Product Datasheet

L3202020 (G10)
FanTastock Label

FACE STOCK

Description	Polyester
Caliper Target (mils)	2
MD Tensile Target (lb/in)	21
CD Tensile Target (lb/in)	28

ADHESIVE

Description	Acrylic Permanent
Caliper Target (mils)	0.8
Peel adhesive Target on Stainless Steel (lb/in)	

LINER

Description	50# SCK
Caliper Target (mils)	3.2

TOTAL CALIPER TARGET (mils) 6

ENVIRONMENT

Storage Temperature (°F)	40	to	80
Storage Humidity (%)	35	to	75
Shelf Life (months)	12		
Minimum Application Temp (°F)	25		
Service Temperature (°F)	-40	to	300

SAMPLE PART # Ask your sales representative for a custom sample.

RIBBON COMPATIBILITY

- TMX1000 Series Wax
- TMX2000 Series Mid-Range
- ✓ TMX3000 Series Resin

COMPLIANCE

- ✓ UL
- ✓ FDA.21 CFR 175.105
- CSA
- cUL

RECOMMENDED FOR SELF-STRIP

NO

MAXIMUM OUTDOOR LIFE

- < 6 months
- < 12 months
- < 18 months
- ✓ 5+ Years

TYPICAL APPLICATIONS

- Shipping / Receiving
- Work in Process (WIP)
- ✓ Rack / Shelf / Bin
- ✓ Point Of Sale
- Lock out / Tag out (LOTO)
- ✓ Asset / Tool Marking

Special Notes

Important Notice: Information presented herein is believed to be accurate based on research with no guarantee of accuracy or completeness. Product must be thoroughly tested under end-use conditions to ensure that it meets all intended requirements. Datasheet does not imply any warranty or guarantee. User assumes all risk and liability in connection with end-use of product.